

**Compur Statox 501 S**  
**Detector for toxic Gases and O<sub>2</sub>**



## Stattox 501 S, for many gas detection applications

Stattox 501 S features safety wherever toxic gases are manufactured, used or are likely to occur as a byproduct. It continuously monitors the atmosphere outdoors or indoors for health threatening concentrations of toxic gases or oxygen deficiency.

This gas detection system is field – proven in the chemical and petrochemical industry, in waste water treatment and manufacturing plants. It operates with electrochemical sensors, which are very specific to the target gas.

The transmitter provides a linear 4 – 20 mA signal, which can be run into a Stattox 503 Control Module or directly into a process control system.

As the electronics are designed intrinsically safe, the sensor head can be opened even in hazardous atmosphere without any extra precautions. This makes calibration or even sensor replacement very easy.

As the sensor head has a digital display, only a gas adapter and a screw driver are needed to do this or to perform a one man calibration.

The system is completed by a complete range of useful accessories, such as splash guards, selectivity filters, heat- and rain shields, horns and flash lights.

### Technical Data

Detectable Gases:	Measuring ranges:
AsH <sub>3</sub>	0 to 0,5 ppm
Cl <sub>2</sub>	0 to 3; 5 ppm
ClO <sub>2</sub>	0 to 1; 5 ppm
CO	0 to 100; 300 ppm
COCl <sub>2</sub>	0 to 0,3; 1,0; 15; 100 ppm
H <sub>2</sub>	0 to 150; 300; 1000 ppm
H <sub>2</sub> S	0 to 100 ppm
HCl	0 to 50 ppm
HCN	0 to 20; 30; 100 ppm
HF	0 to 10 ppm
N <sub>2</sub> H <sub>4</sub>	0 to 1,0 ppm
NH <sub>3</sub>	0 to 150 ppm
NO <sub>2</sub>	0 to 10; 50 ppm
O <sub>2</sub>	2 to 35 Vol. %
O <sub>3</sub>	0 to 1,0 ppm
PH <sub>3</sub>	0 to 1,0 ppm
SO <sub>2</sub>	0 to 5; 20 ppm

Power supply	24 V/DC
Output signal	4 – 20 mA
Operation temperature	- 20 bis + 50°C
Humidity	20 – 95 % r. H.
Weight	0,47 kg
Dimensions	145 x 120 x 85 mm
Material	ABS chromium plated
Protection class	IP 54
Approval	EEx ib IIC T5/6



Sensor head



Stattox 503 Control Module

### Compur Monitors GmbH & Co. KG

Weißenseestraße 101  
D-81539 München  
Tel.: ++49 89 62038-0  
Fax: ++49 89 62038-184  
Email: [compur@compur.de](mailto:compur@compur.de)  
Internet: [www.compur.com](http://www.compur.com)

Specifications are subject to change without notice, and are provided only for comparison of products. The conditions, under which our products are used, are beyond our control. Therefore, the user must fully test our products and/or information to determine suitability for any intended use, application, condition or situation. All information is given without warranty or guarantee. Compur Monitors disclaims any liability, negligence or otherwise, incurred in connection with the use of the products and information. Any statement or recommendation not contained herein is unauthorized and shall not bind Compur Monitors. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or device or its use. No licence is implied or in fact granted under the claims of any patent. Instruments are manufactured by Compur Monitors GmbH & Co. KG, Munich.  
The General Conditions of Supply and Service of Compur Monitors GmbH & Co. KG are applicable. 12/2018